

HaloFogger®

The HaloFogger delivers complete surface disinfection at the touch of a button. This unit is designed for typical room sizes in the Healthcare industry, Senior living Centers, Daycare facilities, Life Science Industry and many other use sites.



HaloFogger® FLX

The HaloFogger FLX combines the volume capability of the standard HaloFogger with the nozzle positioning flexibility of the HaloFogger EXT to provide extended range and variable locating options, even outside the treatment area. This unit is ideal for crawl spaces, attics, HVAC ducts as well as treating multiple rooms or vehicles in rapid succession.



HaloFogger® EXT

The multi-purpose HaloFogger EXT provides flexible nozzle positioning capability to treat a range of smaller spaces. This unit is ideal for treating lab hoods, isolators, ambulances, and vehicles



Treatment Room Size	up to 9,500 ft ³ / 270m ³	up to 9,500 ft ³ / 270m ³	up to 2,500 ft ³ / 70m ³
Timer	10 - 60 minutes	10 - 60 minutes	1 - 30 minutes
Fluid Output	50 ml (1.7 oz) / minute	50 ml (1.7 oz) / minute	25 ml (0.85 oz) / minute
Hose Length	n/a	12 foot	5 foot

HaloFogger Specifications

Dimensions	Height 40 in / 101.5 cm Width 13.25 in / 33.5 cm Depth 18.5 in / 47 cm
Weight	50 lbs / 22.5 kg (without disinfectants)
Reservoir	Max 2 gallons / 7.58 liter

Power Requirements	North America 110Volt, Frequency 50 Hz, Power 350 Watt International 220Volt, Frequency 50/60 Hz, Power 350 Watt
Certification	MET UL 969, MET CE
<i>All devices are manufactured in an FDA registered, GMP compliant facility</i>	

Target Dose Concentration	11ml/m ³
Average coverage per gallon of disinfectant	11,500 ft ³ / 325 m ³
Average coverage per liter of disinfectant	3,000 ft ³ / 86 m ³